



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

SAFETY DATA SHEET (SDS)

Xanthan Gum *SDS*

REV 1.0
31 JULY 2026
GHS REV.11 (2025)

CAS **11138-66-2** EC **234-394-2** SIGNAL WORD **DANGER**

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY

Product Name	Xanthan Gum
Product Type	Microbial polysaccharide (hydrocolloid) powder
Chemical Family	Polysaccharide gum
CAS No.	11138-66-2
EC No.	234-394-2
Other Identifiers	E 415 (EU food additive); INS 415
Molecular Formula	(C35H49O29) _n — repeat unit (PubChem CID 7107). The polymer chain is of the order of 10 ⁶ daltons; the repeat-unit mass of 933.7 g/mol is not a molecular weight for the substance as supplied.
Intended Use	Industrial / professional use as listed on the SPC product page — thickening, stabilising and suspending agent.
Restrictions on Use	Industrial / professional use only. Confirm grade suitability before food, pharmaceutical or other regulated use; FCC / E 415 conformity must be specified on order.
Supplier	Supreme Petro Chemicals
Address	No. 145, 1st Floor, Raja Muthiah Road, Periyamet, Chennai – 600003, India
Emergency Contact	Sanketh — +91 86087 80096 · Sudarshan — +91 81979 47045
Email	admin@supremepetrochemicals.com
Product Page	https://www.supremepetrochemicals.com/products/xanthan-gum
SDS Revision	July 2026
SDS Version	1.0

SECTION 2 HAZARD IDENTIFICATION

Not classified as hazardous under GHS. Combustible dust precautions apply.



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

GHS Classification	Not classified as hazardous — no health, physical (other than combustible dust) or environmental hazard class assigned in the manufacturer SDSs reviewed.
Signal Word	Not classified under UN GHS or EU CLP. The US OSHA Hazard Communication Standard treats the material as a combustible dust and applies the signal word Warning (CP Kelco KELZAN SDS §2).
GHS Pictograms	No GHS pictogram (Not classified). CP Kelco KELZAN SDS §2.2 records Symbols/Pictograms: None.
Hazards Not Otherwise Classified	Combustible dust may form combustible (explosive) dust–air mixtures; dust explosion class St1. Spilled powder is slippery and can cause falls if walked on.

HAZARD STATEMENTS

- None — xanthan gum is not classified as hazardous under UN GHS or EU CLP (Jungbunzlauer Xanthan Gum SDS v1.4, 11-Dec-2021 §2; CP Kelco KELZAN SDS rev. 1.2, 27-Jun-2017 §2).
- May form combustible dust concentrations in air — US OSHA HCS combustible–dust entry only (CP Kelco KELZAN SDS §2.2).

PRECAUTIONARY – PREVENTION

- P210 — Keep away from heat, hot surfaces, sparks, open flames. No smoking.
- P233 — Keep container tightly closed.
- P240 — Ground/bond container and receiving equipment.
- P260 — Do not breathe dust.
- P264 — Wash hands and exposed skin thoroughly after handling.
- P271 — Use only outdoors or in a well-ventilated area.
- P280 — Wear protective gloves and eye protection where dust is generated.
- Take precautionary measures against static discharge; combustible dust may form combustible (explosive) dust–air mixtures.

PRECAUTIONARY – RESPONSE / STORAGE / DISPOSAL

- P304+P340 — IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 — IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P337+P313 — If eye irritation persists: Get medical advice/attention.
- P302+P352 — IF ON SKIN: Wash with plenty of water.



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

- P312 — Call a POISON CENTER or doctor if you feel unwell.
- P402+P404 — Store in a dry place. Store in a closed container.
- P403+P235 — Store in a well-ventilated place. Keep cool.
- P501 — Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	EC NO.	% W/W	GHS CLASSIFICATION
Xanthan Gum	11138-66-2	234-394-2	100	Not classified as hazardous under GHS. No harmonised CLP (Annex VI) entry identified in reviewed sources.

Percentages are by weight. Full text of H-statements listed in Section 16. Substance identity per 21 CFR 172.695 — a polysaccharide gum derived from *Xanthomonas campestris* by pure-culture fermentation and purified by recovery with isopropyl alcohol. EC No. 234-394-2 taken from the CP Kelco KELZAN SDS rev. 1.2 §15 global inventory table.

SECTION 4 FIRST AID MEASURES

Inhalation	Remove person to fresh air. Dust may cause mechanical irritation of the upper respiratory tract. If breathing is difficult, keep at rest in a position comfortable for breathing. If coughing or irritation persists, seek medical attention.
Skin Contact	Brush off dry powder, then wash affected skin with plenty of soap and water. Prolonged or repeated contact may dry the skin and cause irritation (CP Kelco KELZAN SDS §11). No skin irritation was observed in animal testing (Jungbunzlauer SDS v1.4 §11).
Eye Contact	Remove contact lenses if present and easy to do. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes (CP Kelco KELZAN SDS §4). Dust contact can cause mechanical irritation. Seek medical attention if irritation persists.
Ingestion	Rinse mouth thoroughly with water. Xanthan gum is practically non-toxic by ingestion and is permitted as a food additive; no specific treatment is normally required. Seek medical advice if a large quantity has been swallowed or if the person feels unwell.
Note to Physician	Treatment should be symptomatic and supportive. No specific antidote is required. Effects observed are mechanical (dust) rather than chemical.



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

SECTION 5 FIREFIGHTING MEASURES

Suitable Extinguishing Media	Water spray (fog), foam, dry chemical or carbon dioxide. Treat as a Class A fire (CP Kelco KELZAN SDS §5).
Unsuitable Media	None known (CP Kelco KELZAN SDS §5.1). As a handling precaution, avoid any technique that disturbs settled powder and raises a dust cloud.
Specific Hazards	Combustible organic powder. It will burn in contact with a flame, tends to smoulder and self-extinguishes when the ignition source is removed (CP Kelco KELZAN SDS §5). It can contain sufficient fines to cause a combustible dust explosion; dust explosion class St1 (Jungbunzlauer SDS v1.4 §9). Combustion produces carbon dioxide, carbon monoxide and unburned hydrocarbons (smoke).
Protective Equipment	Wear self-contained breathing apparatus (SCBA) and chemical protective clothing. Keep upwind.
Special Procedures	Do not disturb accumulated dust on ledges, beams and equipment. Water mist may be used to cool closed containers. Water applied to the product makes it extremely slippery — take care on floors and walkways. Prevent large volumes of contaminated runoff from entering drains and watercourses.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions	Keep unauthorised personnel away. Ensure adequate ventilation and avoid dust formation. Wear appropriate PPE (see Section 8). Use non-sparking tools, eliminate ignition sources and earth handling equipment. Warn others of the slipping hazard.
Environmental Precautions	Avoid runoff to waterways and sewers. Xanthan gum is readily biodegradable but exerts a high oxygen demand (BOD within 5 days $\approx$ 200 mg/g, Jungbunzlauer SDS v1.4 §12; COD $\approx$ 1600 mg O ₂ /g, CP Kelco KELZAN SDS §12), so bulk discharge can deoxygenate receiving water. German water hazard class WGK 1 (CP Kelco KELZAN SDS §12).
Containment / Clean-up	Small spill: vacuum with dust-safe equipment or sweep gently into labelled, closeable containers. Do not dry sweep in a way that raises dust and do not use compressed air. Large spill: the manufacturer advises wetting the dust with water before sweeping, or vacuum collection (CP Kelco KELZAN SDS §6.3) — note that wetted xanthan



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

gum forms an extremely slippery gel, so restrict water use to what is needed for dust suppression and barrier the area. Water wash-down is not recommended unless the spilled material is already wet.

Reference to Sections

See Section 8 for PPE, Section 13 for disposal, and Section 15 for regulatory information.

SECTION 7 HANDLING AND STORAGE

Handling Precautions

Minimise dust generation and accumulation. Use local exhaust ventilation at transfer and bag-tipping points. Use non-sparking tools. Earth and bond equipment to prevent build-up of electrostatic charge. Keep away from heat, sparks, open flames and hot surfaces.

Hygiene

Wash hands and exposed skin after handling. Do not eat, drink or smoke when using this product. Remove contaminated clothing before reuse.

Storage Conditions

Store in intact original packaging in a clean, dry, cool, well-ventilated place. Keep the container tightly closed and dry — the powder hydrates and cakes if exposed to moisture. Keep off the floor on pallets.

Storage Temperature

Ambient. No specific temperature limit is stated in the reviewed sources; avoid heat sources and direct sunlight.

Incompatible Materials

Strong oxidising agents — listed under conditions to avoid in the CP Kelco KELZAN SDS §10.4. The Jungbunzlauer SDS v1.4 §10 records incompatible materials as 'not applicable'.

Segregation

Do not store with poisonous, harmful or corrosive substances (FUFENG® E415 200MESH specification, storage instruction). Store away from incompatible materials (CP Kelco KELZAN SDS §7.2).

Shelf Life

24 months from date of manufacture in intact original packaging under the storage conditions above (FUFENG® and Deosen published grade sheets).

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limit

OSHA has not established a specific exposure limit for this material; apply the limits for particulates not otherwise regulated (PNOR), which are the least stringent limits applicable to dusts (CP Kelco KELZAN SDS §8). NOTE: the same sheet cites an ACGIH TWA of 0.1



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

mg/m³ for CAS 11138–66–2. That figure could not be corroborated against ACGIH and is roughly two orders of magnitude below ACGIH's general particulates (PNOG) guidance, so it is not adopted here. Verify the applicable local limit (OSHA / NIOSH / ACGIH / EU / India). PNEC and DNEL: no information available.

Engineering Controls

Provide a good standard of controlled ventilation (5 to 10 air changes per hour) and local exhaust ventilation at all dust-generating points; enclose transfer where practical (CP Kelco KELZAN SDS §8.2). Adopt combustible-dust housekeeping — prevent accumulation on surfaces, use dust-safe vacuums, do not blow down with compressed air. Provide eyewash facilities in the work area.

Respiratory Protection

Where dust levels are not controlled by ventilation, use a NIOSH/EN-approved particulate respirator (P95 or P100 / FFP2 or FFP3). Use SCBA for emergency and fire situations.

Hand / Eye / Skin

Hands: impervious gloves for operations where prolonged or repeated skin contact may occur; the powder is drying to skin on repeated contact. Eyes: EN 166 / ANSI Z87.1 safety glasses with side shields, or dust goggles where dust is generated. Skin: suitable protective clothing and safety footwear with good grip — wetted product is extremely slippery.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance

White to cream / light yellow free-flowing powder. Sources describe it as 'off-white, beige' (Jungbunzlauer SDS v1.4 §9), 'white to light tan' (CP Kelco KELZAN SDS §9) and 'cream-white' / 'cream colored' (FUFENG® and Deosen grade sheets).

Odour

Odourless to faintly characteristic. Sources conflict — Jungbunzlauer SDS v1.4 §9 states 'characteristic'; CP Kelco KELZAN SDS §9 states 'odorless'.

Odour Threshold

Not determined (Jungbunzlauer SDS v1.4 §9).

pH

6.0–8.0 (1% aqueous solution) per the FUFENG® and Deosen 200 mesh grade sheets. The Jungbunzlauer SDS v1.4 §9 gives a wider range of 5.5–8.5. Verify from supplier COA for specific grade.

Melting / Freezing Point

Decomposes without melting (Jungbunzlauer SDS v1.4 §9).

Boiling Point / Range

Not applicable — non-volatile solid polymer (Jungbunzlauer SDS v1.4 §9).



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

Decomposition Temperature	No data available (Jungbunzlauer SDS v1.4 §9).
Flash Point	Not applicable (Jungbunzlauer SDS v1.4 §9; CP Kelco KELZAN SDS §9). The solid does not ignite in the flammability (solid) test.
Auto-ignition Temperature	Not applicable (Jungbunzlauer SDS v1.4 §9).
Flammability / Explosion Limits	Upper and lower explosion limits: no data available. Not explosive as a substance; dust explosion class St1 (Jungbunzlauer SDS v1.4 §9).
Vapour Pressure	Not applicable — non-volatile solid polymer.
Vapour Density (air = 1)	Not applicable (solid).
Density / Relative Density	No data available (Jungbunzlauer SDS v1.4 §9 records both density and relative density as 'no data available'). Bulk density is grade- and grind-dependent — verify from supplier COA/TDS.
Solubility in Water	Completely soluble — disperses and hydrates in cold or hot water to a high-viscosity pseudoplastic solution (Jungbunzlauer SDS v1.4 §9; CP Kelco KELZAN SDS §9).
Solubility, Other Solvents	Alcohol: insoluble, dispersible (Jungbunzlauer SDS v1.4 §9).
Partition Coefficient (log Pow)	No data available (Jungbunzlauer SDS v1.4 §9; CP Kelco KELZAN SDS §9). Partitioning into an organic phase is not expected for a high-molecular-weight polysaccharide.
Viscosity	Kinematic viscosity not applicable to the powder as supplied (Jungbunzlauer SDS v1.4 §9). Solution viscosity for this grade is 1200–1700 cps measured as a 1% solution in 1% KCl — a viscosity figure is meaningless unless the medium and method are stated. Verify from supplier COA for specific grade.
Particle Size	200 mesh grade — 99% min through 80 mesh (180 µm); through 200 mesh (75 µm) per the agreed order specification (published grades guarantee 92% min). Verify from supplier COA for specific grade.
Oxidising Properties	No oxidising effect (Jungbunzlauer SDS v1.4 §9).
VOC Content	Nil — non-volatile solid.

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage and handling conditions. No decomposition if stored and applied as directed (Jungbunzlauer SDS v1.4 §10; CP Kelco KELZAN SDS §10.2).
Conditions to Avoid	Dust formation and dust accumulation; heat, sparks and open flame; strong oxidising agents (CP Kelco KELZAN SDS §10.4). Also avoid



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

	moisture, which causes hydration and caking, and build-up of electrostatic charge.
Incompatible Materials	Strong oxidising agents (CP Kelco KELZAN SDS §10.4). The Jungbunzlauer SDS v1.4 §10 records incompatible materials as 'not applicable'. No other incompatibilities located in the sources reviewed.
Hazardous Decomposition	None known under normal storage and handling (CP Kelco KELZAN SDS §10.6). In a fire or at high temperature: carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke) (Jungbunzlauer SDS v1.4 §10).
Hazardous Reactions	No hazardous polymerisation. Stable under recommended storage conditions; no hazards to be specially mentioned other than that dust may form an explosive mixture in air (Jungbunzlauer SDS v1.4 §10).

SECTION 11 TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	LD ₅₀ (rat, oral): > 5,000 mg/kg (CP Kelco KELZAN SDS §11, limit test). Jungbunzlauer SDS v1.4 §11 reports LD ₅₀ oral 45,000 mg/kg (rat) and 20,000 mg/kg (mouse). Sources differ in magnitude but agree that classification criteria for acute toxicity are not met.
Acute Dermal Toxicity	No numeric endpoint located in the sources reviewed; Jungbunzlauer SDS v1.4 §11 records 'no skin irritation'. No systemic toxicity is expected by the dermal route.
Acute Inhalation Toxicity	An LC ₅₀ could not be determined — no mortality was observed at the maximum achievable concentration (rat, 21 mg/L, 1 h exposure; Jungbunzlauer SDS v1.4 §11). CP Kelco KELZAN SDS §11 records inhalation LC ₅₀ > 21 mg/L against rabbit; the species difference between the two sources is noted rather than merged.
Skin Irritation	No skin irritation observed (rat, 360 h; rabbit, 120 h — Jungbunzlauer SDS v1.4 §11). Prolonged or repeated contact with dust may dry the skin and cause irritation (CP Kelco KELZAN SDS §11); this is a mechanical/physical effect.
Eye Irritation	No eye irritation observed (rat, 120 h — Jungbunzlauer SDS v1.4 §11). Dust contact with the eyes can lead to mechanical irritation (CP Kelco KELZAN SDS §11).
Sensitisation	Did not cause sensitisation in laboratory animals (guinea pig — Jungbunzlauer SDS v1.4 §11). Not a skin sensitiser; respiratory



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

	sensitisation classification criteria not met (CP Kelco KELZAN SDS §11).
Carcinogenicity	Not classifiable as a human carcinogen (Jungbunzlauer SDS v1.4 §11). Not listed by IARC, NTP or OSHA as a carcinogen, and not listed under California Proposition 65 (CP Kelco KELZAN SDS §15).
Mutagenicity	Animal testing did not show any mutagenic effects (Jungbunzlauer SDS v1.4 §11).
Reproductive Toxicity	Not classified based on available information; no data available (Jungbunzlauer SDS v1.4 §11). CP Kelco KELZAN SDS §11 records that the classification criteria are not met.
Repeated Dose Toxicity	No adverse effect has been observed in chronic toxicity tests (rat, oral — Jungbunzlauer SDS v1.4 §11). STOT single and repeated exposure: no data available.

SECTION 12 ECOLOGICAL INFORMATION

Aquatic Toxicity	Fish: LC ₅₀ (Oncorhynchus mykiss, 96 h) 420 mg/L with no adverse effect observed in acute toxicity tests (Jungbunzlauer SDS v1.4 §12); CP Kelco KELZAN SDS §12 reports 490 mg/L for the same species and a 48 h EC ₅₀ (Daphnia magna) of 980 mg/L. Not considered harmful to aquatic life; no aquatic hazard class assigned in Section 2. Jungbunzlauer records no data for daphnia, algae and micro-organisms.
Persistence / Degradability	Readily biodegradable — 78% in 28 days, OECD Test Guideline 301F (Jungbunzlauer SDS v1.4 §12). BOD within 5 days ≈ 200 mg/g (Jungbunzlauer SDS v1.4 §12); BOD ≈ 200 mg O ₂ /g and COD ≈ 1600 mg O ₂ /g (CP Kelco KELZAN SDS §12). Because the material is biodegradable, aqueous formulations normally require a preservative.
Bioaccumulation	Accumulation is not expected — the product is readily biodegradable in both water and soil (Jungbunzlauer SDS v1.4 §12). Does not meet the criteria for PBT or vPvB (CP Kelco KELZAN SDS §12.5).
Mobility in Soil	No data available on distribution among environmental compartments (Jungbunzlauer SDS v1.4 §12; CP Kelco KELZAN SDS §12.4). Readily biodegradable in soil.
Other Adverse Effects	German water hazard class WGK 1 (CP Kelco KELZAN SDS §12). Bulk discharge to water exerts a high oxygen demand and can



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

deoxygenate receiving water — avoid uncontrolled release.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste from Product	Non-hazardous organic solid. Dispose of in accordance with local and national regulations; where possible recycling is preferred to disposal or incineration (Jungbunzlauer SDS v1.4 §13). Do not discharge significant quantities to drain untreated — the high BOD/COD load can overload effluent treatment and deoxygenate receiving water.
Waste Codes	Waste codes should be assigned by the user based on the application for which the product was used. The CP Kelco KELZAN SDS §13 lists European Waste Catalogue code 16 03 06 for xanthan gum.
Contaminated Packaging	Empty paper bags, fibre drums and cartons carry only powder residues. Take empty containers to an approved waste handling site for recycling or disposal (CP Kelco KELZAN SDS §13). Do not reuse food-grade packaging for other materials.
Indian Regulations	Follow applicable rules under the Environment Protection Act and SPCB/CPCB requirements. Assign the waste code according to the actual process and the local regulatory schedule.

SECTION 14 TRANSPORT INFORMATION

PARAMETER	UN / ADR (ROAD)	IMDG (SEA)	IATA (AIR)
UN Number	Not regulated	Not regulated	Not regulated
Proper Shipping Name	Not regulated	Not regulated	Not regulated
Class	Not regulated	Not regulated	Not regulated
Packing Group	Not regulated	Not regulated	Not regulated
Marine Pollutant	No	No	—
EmS / Tunnel Code	Not applicable	Not applicable	—

Xanthan gum (CAS 11138-66-2) is not a dangerous good. CP Kelco KELZAN SDS rev. 1.2 §14 records 'Not regulated' for TDG-Canada, US DOT, ADR, RID, ADN, IATA, IMDG/IMO and ICAO, with UN number, proper shipping name, transport hazard class and packing group all 'None' and environmental hazards 'No'; Jungbunzlauer SDS v1.4 §14 agrees for IATA-DGR, IMDG and DOT. Transport in bulk under MARPOL 73/78 Annex II and the IBC Code is not applicable for the product as supplied. It moves as general cargo in standard commercial packaging. Verify current carrier, modal and destination rules before each shipment.



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

SECTION 15 REGULATORY INFORMATION

EU / REACH / CLP

Not classified under CLP Regulation (EC) No 1272/2008 based on the manufacturer SDSs reviewed. No harmonised (Annex VI) classification for xanthan gum was identified; confirm the current ECHA C&L Inventory position before reliance. The CP Kelco KELZAN SDS §15 records the REACH registration status as 'Exempt'. Permitted food additive E 415 under Regulation (EC) No 1333/2008. Observe REACH Annex II SDS requirements.

OSHA (USA)

Prepared in OSHA HCS / HazCom 2012 aligned 16-section format. The only applicable hazard entry is Combustible Dust (signal word Warning, no pictogram); SARA 311/312 hazard: combustible dust (Jungbunzlauer SDS v1.4 §15). Approved as a direct food additive under 21 CFR 172.695, which limits residual isopropyl alcohol to 750 ppm and requires a minimum 1% viscosity in 1% KCl of 600 cP with a viscosity ratio of 1.02–1.45. Listed on the TSCA inventory (CP Kelco KELZAN SDS §15); verify current TSCA status before US import or distribution.

India

Observe applicable Indian regulations including the Environment Protection Act and SPCB/CPCB requirements. Where the material is intended for food use, FSSAI food additive requirements apply (INS 415) and an FCC / E 415 conforming grade with the corresponding certificate pack must be specified on order.

Other Jurisdictions

Listed on or in compliance with the AICS (Australia), DSL (Canada), IECSC (China), ENCS/ISHL (Japan), KECI (South Korea), PICCS (Philippines), NZIoC (New Zealand) and TCSI (Taiwan) inventories per the reviewed manufacturer SDSs. Canada: WHMIS status recorded as 'not regulated' (CP Kelco KELZAN SDS §15); bilingual SDS/label may be required. Check local food additive approvals before export or import.

SECTION 16 OTHER INFORMATION

Prepared By

Supreme Petro Chemicals — Technical Department

SDS Standard

UN GHS; OSHA HCS/HazCom; EU CLP/REACH Annex II; Canada WHMIS/HPR — 16-section format

Revision Date

31 July 2026



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL CHEMICALS ·
SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 86087 80096 · +91 81979 47045
admin@supremepetrochemicals.com

Version	1.0 (first issue)
Key Sources	Jungbunzlauer Xanthan Gum Safety Data Sheet, Version 1.4 US/EN, revision date 11 December 2021, SDS No. 1000000000005 (first issue 16 June 2017); CP Kelco U.S., Inc. KELZAN® Safety Data Sheet, Revision Number 1.2, issue date 27 June 2017; FUFENG® E415 200MESH xanthan gum specification sheet; Deosen Biochemical (Ordos) Ltd. Ziboxan® F200 specification, Specs # DSXG02, Version # 013, issue date 01 January 2025; US FDA 21 CFR 172.695; PubChem CID 7107. All accessed July 2026.
Known Data Gaps	Density and relative density, decomposition temperature, auto-ignition data, dust LEL/UEL and soil mobility: no data available in the reviewed sources. Odour, acute oral LD ₅₀ magnitude, acute inhalation test species, pH range and incompatible materials differ between the two manufacturer SDSs; both positions are recorded above rather than merged. No harmonised CLP (Annex VI) entry was verified directly on the ECHA C&L Inventory.
Disclaimer	Information is given in good faith and believed accurate at issue. It does not constitute a specification or guarantee; the user is responsible for safe use, handling and compliance with all applicable laws and regulations. Supreme Petro Chemicals shall not be liable for any loss, injury or damage resulting from reliance on this information.

FULL TEXT OF H-STATEMENTS

- None — xanthan gum (CAS 11138-66-2) carries no GHS Hazard Statements under UN GHS or EU CLP based on the sources reviewed.
- May form combustible dust concentrations in air — US OSHA HCS combustible-dust entry; not a UN GHS or CLP hazard statement.