



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL
CHEMICALS · SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 81979 47045 · +91 86087 80096
Admin@supremepetrochemicals.com

TECHNICAL DATA SHEET

Butyl Cellosolve (*Ethylene Glycol Monobutyl Ether*)

DOC SPC-TDS-GLY-005
Rev 01 · 10 June 2026

CAS **111-76-2** HSN **2909 43 00** GRADE **Solvent Grade**

MANUFACTURED BY

Dow Chemical

Butyl CELLOSOLVE Solvent — fast-evaporating glycol ether; globally specified for coatings & cleaners

NO	PARAMETER	UNIT	SPECIFICATION
01	Butyl Cellosolve Purity	% wt	99.0 min
02	Water Content	% wt	0.10 max
03	Acidity (as Acetic Acid)	% wt	0.010 max
04	Colour, Pt-Co	Pt-Co scale	10 max
05	Specific Gravity at 20/20 °C	—	0.9005 – 0.9040

HANDLING

Combustible liquid (UN 2369, Class 3); harmful if swallowed or inhaled, may cause skin/eye irritation — use with adequate ventilation and protective gloves/goggles.

PACKAGING (AS SUPPLIED)

MS drums

For current pricing, availability or a Certificate of Analysis for Butyl Cellosolve: call or WhatsApp **+91 81979 47045 · +91 86087 80096**, or see Supremepetrochemicals.com/products/butyl-cellosolve-glycol. Quotes are typically answered within 4 working hours (Mon–Sat).

All specification values in this document are reproduced from the manufacturer's published specification (Dow) cross-checked with batch COA, cross-checked against the manufacturer's published documentation and Certificate of Analysis. Supreme Petro Chemicals provides this Technical Data Sheet in good faith for reference only and accepts no liability for errors, omissions, or subsequent revisions by the manufacturer; the manufacturer's current documentation prevails. This is not a Certificate of Analysis — a batch-specific CoA accompanies every consignment.