



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL
CHEMICALS · SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 81979 47045 · +91 86087 80096
Admin@supremepetrochemicals.com

TECHNICAL DATA SHEET

Chlorinated Paraffin *Wax*

DOC SPC-TDS-PLA-004
Rev 01 · 10 June 2026

CAS **63449-39-8** HSN **38249900** GRADE **Liquid, ~52% Chlorine**

MANUFACTURED BY

Suntek Chlorides Private Limited

ISO-certified plasticizer manufacturer

NO	PARAMETER	UNIT	SPECIFICATION
01	Appearance		Pale yellow viscous liquid
02	Colour (Hazen)	max	50
03	Specific Gravity	@27C	1.400 +/- 0.02
04	Chlorine Content	%	~52
05	Viscosity (Ford Cup 6mm)	Poise	25 - 75
06	Free Mineral Acidity	% max	0.01
07	Free Chlorine	ppm	Nil
08	Volatile Loss (130C/3h)	% max	0.80
09	Thermal Stability (175C/4h)	% HCl max	0.20
10	Heat Stability (180C/20min)		Light yellow
11	Refractive Index	min	>1.49

HANDLING

Low toxicity; keep away from heat, strong oxidisers and open flame. Store in cool, dry, ventilated area in sealed drums.

PACKAGING (AS SUPPLIED)

250 kg HDPE drums

For current pricing, availability or a Certificate of Analysis for Chlorinated Paraffin Wax (CPW): call or WhatsApp **+91 81979 47045 · +91 86087 80096**, or see Supremepetrochemicals.com/products/chlorinated-paraffin-wax-cpw. Quotes are typically answered within 4 working hours (Mon–Sat).

All specification values in this document are reproduced from the Manufacturer COA cross-checked with published CPW-52 grade specification., cross-checked against the manufacturer's published documentation and Certificate of Analysis. Supreme Petro Chemicals provides this Technical Data Sheet in good faith for reference only and accepts no liability for errors, omissions, or subsequent revisions by the manufacturer; the manufacturer's current documentation prevails. This is not a Certificate of Analysis — a batch-specific CoA accompanies every consignment.