



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL
CHEMICALS · SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,

Periyamet, Chennai – 600003, India

+91 81979 47045 · +91 86087 80096

Admin@supremepetrochemicals.com

TECHNICAL DATA SHEET

Maleic Anhydride (*Briquettes / Flakes*)

DOC SPC-TDS-ANH-002

Rev 01 · 10 June 2026

CAS **108-31-6**

HSN **2917 14 00**

GRADE **IS 5149:2020**

MANUFACTURED BY

IG Petrochemicals Limited (IGPL)

Taloja MIDC, Maharashtra, India — India's largest maleic anhydride manufacturer; ISO certified

NO	PARAMETER	UNIT	SPECIFICATION
01	Maleic Anhydride Content	% mass	99.2 min
02	Maleic Acid Content	% mass	0.8 max
03	Crystallizing Point	°C	52.1 min
04	Colour of Molten Material	APHA	20 max
05	Ash	% mass	0.005 max
06	Iron (as Fe)	ppm	10 max
07	Appearance	—	White flakes, no visible impurities

HANDLING

Corrosive solid; causes severe skin burns and eye damage, may cause respiratory sensitisation. Keep dry and away from moisture/water; use respiratory protection, gloves and goggles when handling.

PACKAGING (AS SUPPLIED)

25 kg bags (white flakes)

For current pricing, availability or a Certificate of Analysis for Maleic Anhydride: call or WhatsApp **+91 81979 47045 · +91 86087 80096**, or see [Supremepetrochemicals.com/products/maleic-anhydride](https://www.supremepetrochemicals.com/products/maleic-anhydride). Quotes are typically answered within 4 working hours (Mon–Sat).

All specification values in this document are reproduced from the manufacturer's certificate of quality (IGPL, IS 5149:2020), cross-checked against the manufacturer's published documentation and Certificate of Analysis. Supreme Petro Chemicals provides this Technical Data Sheet in good faith for reference only and accepts no liability for errors, omissions, or subsequent revisions by the manufacturer; the manufacturer's current documentation prevails. This is not a Certificate of Analysis — a batch-specific CoA accompanies every consignment.