



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL
CHEMICALS · SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,

Periyamet, Chennai – 600003, India

+91 81979 47045 · +91 86087 80096

Admin@supremepetrochemicals.com

TECHNICAL DATA SHEET

Mineral Turpentine Oil

DOC SPC-TDS-PET-001

Rev 01 · 10 June 2026

CAS 64475-85-0

HSN 27101990

GRADE IS 1745:2018

MANUFACTURED BY

Chennai Petroleum Corporation Limited (CPCL)

Group company of Indian Oil

NO	PARAMETER	UNIT	SPECIFICATION
01	Density @15C	kg/m3	Reported (~802)
02	Distillation IBP	C min	125.0
03	Distillation 50%	C	Reported
04	Distillation 95%	C	Reported
05	Final Boiling Point	C max	240.0
06	Flash Point (Abel)	C min	30
07	Colour (Saybolt)	min	21
08	Aromatic Content	% (V) max	40.0
09	Copper Strip Corrosion (3h/50C)		Not worse than No.1
10	Residue on Evaporation	mg/100ml max	5.00

HANDLING

Flammable liquid. Keep away from heat, sparks and open flame. Store in cool, well-ventilated area; use bonded/grounded containers.

PACKAGING (AS SUPPLIED)

Bulk tanker / 200 L drums

For current pricing, availability or a Certificate of Analysis for Mineral Turpentine Oil (MTO): call or WhatsApp +91 81979 47045 · +91 86087 80096, or see [Supremepetrochemicals.com/products/mineral-turpentine-oil-mto](https://supremepetrochemicals.com/products/mineral-turpentine-oil-mto). Quotes are typically answered within 4 working hours (Mon–Sat).

All specification values in this document are reproduced from the CPCL Manali Refinery test report cross-checked with IS 1745:2018., cross-checked against the manufacturer's published documentation and Certificate of Analysis. Supreme Petro Chemicals provides this Technical Data Sheet in good faith for reference only and accepts no liability for errors, omissions, or subsequent revisions by the manufacturer; the manufacturer's current documentation prevails. This is not a Certificate of Analysis — a batch-specific CoA accompanies every consignment.