



SUPREME PETRO CHEMICALS

IMPORTER & DISTRIBUTOR OF INDUSTRIAL
CHEMICALS · SINCE 1997

No. 145, 1st Floor, Raja Muthiah Road,
Periyamet, Chennai – 600003, India
+91 81979 47045 · +91 86087 80096
Admin@supremepetrochemicals.com

TECHNICAL DATA SHEET

Paraffin Wax (*Hard / Light*)

DOC SPC-TDS-PET-005
Rev 01 · 10 June 2026

CAS **8002-74-2** HSN **2712 20 00** GRADE **Fully Refined, IS 4654**

MANUFACTURED BY

Chennai Petroleum Corporation Limited (CPCL)

Manali Refinery, Chennai — Government of India Enterprise (group company of IndianOil)

NO	PARAMETER	UNIT	SPECIFICATION
01	Appearance	—	White, translucent slab
02	Congeaing / Melting Point	°C	58 – 62
03	Oil Content	% mass	0.5 max
04	Colour (Saybolt)	—	+28 min
05	Penetration at 25 °C	0.1 mm	18 max
06	Odour	—	Nil to faint
07	Acidity / Alkalinity	—	Nil
08	Flash Point (COC)	°C	200 min

HANDLING

Combustible solid; molten wax causes thermal burns. Store away from heat and open flame; handle molten product with heat-resistant gloves and avoid skin contact.

PACKAGING (AS SUPPLIED)

50 kg slabs / HDPE-lined bags

For current pricing, availability or a Certificate of Analysis for Paraffin Wax (Hard / Light): call or WhatsApp **+91 81979 47045 · +91 86087 80096**, or see Supremepetrochemicals.com/products/paraffin-wax-hard-light. Quotes are typically answered within 4 working hours (Mon–Sat).

All specification values in this document are reproduced from the manufacturer's published specification (IS 4654 — fully refined paraffin wax), cross-checked against the manufacturer's published documentation and Certificate of Analysis. Supreme Petro Chemicals provides this Technical Data Sheet in good faith for reference only and accepts no liability for errors, omissions, or subsequent revisions by the manufacturer; the manufacturer's current documentation prevails. This is not a Certificate of Analysis — a batch-specific CoA accompanies every consignment.